

# ECS4120 Series

## L2+/L3 Lite Gigabit Ethernet Access / Aggregation Switch with 4 10G Uplinks



### Product Overview

The Edgecore ECS4120 switch series is a Gigabit Ethernet access switch with four 10G uplink ports. The switch is ideal for Internet Service Providers (ISPs) and Multiple System Operators (MSOs) to provide home users with triple-play services with up to Gigabit bandwidth. It is also an ideal Gigabit access switch for SMB, enterprise, and campus networks. The ECS4120 switch series is packed with features that bring high availability, comprehensive security, robust multicast control, and advance QoS to the network edge, while maintaining simple management. The switch also supports the most advance IPv6 management, IPv6 security, and IPv6 multicast control in accordance with the growth of IPv6 deployment. ISPs can expand their services from home to business users by providing a more reliable and resilient network (ITU-T G.8032 ERPS), L2 VPNs, and advanced OAM (Operations, Administration, and Maintenance) functions to ensure service-level agreements.

### Key Features and Benefits

#### Performance and Scalability

The Edgecore ECS4120 Series is a high-performance Gigabit Ethernet L2+/L3 Lite managed switch with 128Gbps/176Gbps switching capacity. The switch delivers wire-speed switching performance on all Gigabit ports, taking full advantage of existing high-performance Gigabit CPEs, PCs, 11n/ac Wi-Fi APs etc, significantly improving the responsiveness of applications and file transfer times.

The four built-in 10G SFP+ ports provide uplink flexibility, allowing the insertion of fiber or copper, Gigabit or 10G transceivers, to create up to 10 Gbps high-speed uplinks to servers or service provider, corporate, or campus networks, reducing bottlenecks and increasing the performance of the access network.

The Voice VLAN function automatically detects VoIP devices by OUI or LLDP and groups the voice traffic into a separate VLAN for better performance. It can also automatically change port priorities, so a higher CoS value can be assigned for guaranteed voice quality.

#### Continuous Availability

The IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability.

The IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base, providing Layer 2 load sharing on redundant links up to 64 instances.

The ECS4120 Series supports IEEE 802.3ad Link Aggregation Control Protocol (LACP). LACP increases bandwidth by automatically aggregating several physical links together as a logical trunk and offers load balancing and fault tolerance for uplink connections.

The ECS4120 Series supports G.8032 Ethernet Ring Protection Switching with the ability for the network to detect and recover from incidents without impacting users, meeting the most demanding quality and availability requirements. Rapid recovery time when problems do occur is as low as 50ms.

#### Reliability and Energy Efficiency

The fanless design of ECS4120-28T ensures noiseless operation and increases the reliability of the system.

The design of the ECS4120 Series incorporates high energy efficiency in order to reduce the impact on the environment. The Green Ethernet power-saving features and fanless design significantly reduce the power consumption.

#### Enhanced Security

Port security limits the total number of devices from using a switch port and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. When a user is authenticated, the VLAN, QoS and security policy are automatically applied to the port where the user is connected, otherwise the port is grouped in a guest VLAN with limited access.

DHCP snooping allows a switch to protect a network from rogue DHCP servers that offer invalid IP addresses.

IP Source Guard prevents people from using IP addresses that were not assigned to them.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on source and destination MAC addresses, IP addresses, or TCP/UDP ports. ACLs are hardware supported, so switching performance is not compromised.

Private VLANs (traffic segmentation per port) isolate edge ports to ensure user privacy.

DAI (Dynamic ARP Inspection) is a security feature that validates Address Resolution Protocol (ARP) packets in a network. DAI allows a network administrator to intercept, log, and discard ARP packets with invalid MAC-to-IP address bindings.

Secure Shell (SSH) and Secure Sockets Layer (SSL/HTTPS) encrypt Telnet and web access to the switch, providing secure network management.

The ECS4120 Series also supports both RADIUS and TACACS+ authentication methods to secure your network.

## Key Features and Benefits

### Comprehensive QoS

The ECS4120 Series offers advanced QoS for marking, classification, and scheduling to deliver best-in-class performance for data, voice, and video traffic at wire speed. Eight egress queues per port enable differentiated management of up to eight traffic types through the switch.

Traffic is prioritized according to 802.1p and DSCP to provide optimal performance for real-time applications. Weighted Round Robin (WRR) and strict priority ensure differential prioritization of packet flows and avoid congestion of ingress and egress queues.

Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allows maximum control of network resources.

The ECS4120 Series supports Three Color Marker and Policing Single rate: Committed Information Rate (CIR) Two rate: CIR + Peak Information Rate (PIR) Traffic Policing: The switch drops or remarks the priority tags of packets when they exceed the burst size.

### Robust Multicast Control

IGMP snooping prevents the flooding of multicast traffic by dynamically configuring switch ports so that multicast traffic is forwarded to only those ports associated with an IP multicast receiver. IGMP increases the performance of networks by reducing multicast traffic flooding.

IGMP groups allow you to create customer packages for IP-TV channels, making switch configuration easy. IGMP Filtering prevents subscribers seeing unsubscribed IP-TV channels. And, IGMP Throttling allows you to set how many IP-TV channels a subscriber can receive simultaneously.

Multicast VLANs are shared in the network, while subscribers remain in separate VLANs. This increases network security and saves bandwidth on core links. Multicast streams do not have to be routed in core L3 switches, which saves CPU power.

Multicast VLAN Registration (MVR) is designed for applications such as Media-on-Demand that send multicast traffic across an Ethernet network.

### IPv6 Support

The switch supports a number of IPv6 features, including IPv6 Management, DCHPv6 Snooping with Option 37, IPv6 Source Guide, and MVR6.

### Superior Management

An industry-standard command-line interface (CLI), accessed through the console port or Telnet, provides a familiar user interface and command set for users to manage the switch.

An embedded user-friendly web interface helps users to quickly and simply configure switches.

The ECS4120 Series supports SNMPv1,2c,3 and four-group RMON. The switch provides a complete private MIB for the configuration of most functions via the SNMP protocol.

Administrators can backup and restore firmware and configuration files via TFTP or FTP. The switch also provides the configuration of auto-provision for ease of use in large deployments.

AAA (Authentication, Authorization and Accounting) via RADIUS, TACACS+, enables centralized control of the switch. You can also authorize access rights per user and account for all actions performed by administrators.

### Service Monitoring and Management

The ECS4120 Series supports IEEE 802.1ag and ITU-T Y.1731, allowing service providers to monitor end-to-end services, identify connectivity and performance issues, and isolate problems from a remote location without dispatching an engineer onsite.

The switch also provides the capability to monitor service availability, delay and delay variation for verifying SLA conformance (for billing purposes) and providing advance indication of performance degradation before a service outage occurs.

### Virtual Private Networks

The ECS4120 Series supports Layer 2 VPNs by using Q-in-Q functions, where an 802.1Q tag from a customer VLAN (called CE-VLAN ID) is encapsulated in a second 802.1Q tag from a service-provider network (called an SP-VLAN ID). The switch supports rewriting the VLAN tag of egress traffic when the ingress traffic is tagged.

The switch also supports Layer 2 Protocol Tunneling for STP, CDP, VTP, PVST+, with Cisco-proprietary multicast address (01-00-0c-cd-cd-d0) replacement.

### PoE Features

The ECS4120-28P can provide up to 30 Watts of power to attached devices, such as VoIP phones, wireless access points, and surveillance cameras etc, all over existing Cat. 5 cables. The switch can deliver up to 30 Watts on 13 ports, or 15.4 Watts on 24 ports.





PoE eliminates the need for individual power sources for devices in the network, saving on costs for power cables and avoiding power outlet availability issues.

If the power demand exceeds the switch's maximum power budget, ports can be prioritized to receive power, and the power allocation is configurable.

The PoE power can be enabled or disabled remotely by setting a time schedule. For example, during off-duty hours all the PoE devices can be shut down for power saving without human intervention.

# ECS4120 Series Product Specifications



www.edge-core.com

Product Model		ECS4120-28T	ECS4120-28F	ECS4120-28P	ECS4120-52T
Product Image					
Port	RJ-45 10/100/1000BASE-T Ports	24	0	24	48
	100/1000BASE-X SFP Ports	0	20	0	0
	Combo Gigabit (RJ-45/SFP) Ports	0	4	0	0
	SFP+ 10 Gigabit Uplink Ports	4	4	4	4
	GE Out-of-Band Management Port	No	1	No	No
	RJ-45 Console Port	1	1	1	1
Performance	Switching Capacity	128 Gpbs	128 Gpbs	128 Gpbs	176 Gpbs
	Forwarding Rate	95 Mpps	95 Mpps	95 Mpps	130 Mpps
	Flash Memory	256 MB	256 MB	256 MB	256 MB
	DRAM	512 MB	512 MB	512 MB	512 MB
	MAC Address Table Size	16 K	16 K	16 K	16 K
	Jumbo Frames	9 KB	9 KB	9 KB	9 KB
	Auto-negotiation, Auto-MDI/MDIX	Yes	Yes	Yes	Yes
PoE	Support on all Gigabit ports based on IEEE 802.3af	No	No	Yes	No
	PoE+ based on IEEE 802.3at	No	No	Yes	No
	Auto disable after exceeding power budget	No	No	Yes	No
	Dynamic Power Allocation	No	No	Yes	No
	PoE Power Budget	No	No	370 W	No
Mechanical	Rack Space	19"	19"	19"	19"
	Dimension (W x D x H) cm	44 x 22 x 4.4	44 x 22 x 4.4	44x 33 x 4.4	44 x 27.9 x 4.4
	Weight	2.35 kg	3.32 kg	4.53 kg	3.72 kg
Power Supply	100-240 VAC, 50-60 Hz	Yes	Yes	Yes	Yes
	DC Power Input (48-60 V)	No	Yes	No	No
	Max System Power Consumption (Watts)	21.48 W	21.48 W	460 W	45.23 W
Environmental	Operating Temperature	0°C to 50°C	0°C to 50°C	0°C to 50°C	0°C to 50°C
	Storage Temperature	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
	Operating Humidity (non-condensing)	10% to 90%	10% to 90%	10% to 90%	10% to 90%
	Storage Humidity (non-condensing)	10% to 90%	10% to 90%	10% to 90%	10% to 90%
	Environmental Regulation Compliance: WEEE	Yes	Yes	Yes	Yes
	Environmental Regulation Compliance: RoHS	Yes	Yes	Yes	Yes
Certification	FCC Class A	Yes	Yes	Yes	Yes
	CE	Yes	Yes	Yes	Yes
	Safety Compliance: CB	Yes	Yes	Yes	Yes
	Safety Compliance: UL	Yes	Yes	Yes	Yes

\*Not support sfp-preferred-auto in ECS4120-28F Combo Ports.

# ECS4120 Series Product Specifications

www.edge-core.com

Product Model		ECS4120-28Fv2	ECS4120-28Fv2-I
Product Image			
Port	RJ-45 10/100/1000BASE-T Ports	0	0
	100/1000BASE-X SFP Ports (Support DDM)	20	20
	Combo Gigabit (RJ-45/SFP) Ports	4	4
	SFP+ 10 Gigabit Uplink Ports	4	4
	GE Out-of-Band Management Port	1	1
	RJ-45 Console Port	1	1
Performance	Switching Capacity	128 Gpbs	128 Gpbs
	Forwarding Rate	95 Mpps	95 Mpps
	Flash Memory	256 MB	256 MB
	DRAM	512 MB	512 MB
	MAC Address Table Size	16 K	16 K
	Jumbo Frames	9 KB	9 KB
	Auto-negotiation, Auto-MDI/MDIX	Yes	Yes
PoE	Support on all Gigabit ports based on IEEE 802.3af	No	No
	PoE+ based on IEEE 802.3at	No	No
	Auto disable after exceeding power budget	No	No
	Dynamic Power Allocation	No	No
	PoE Power Budget	No	No
Mechanical	Rack Space	19"	19"
	Dimension (W x D x H) cm	44 x 22 x 4.4	44 x 22 x 4.4
	Weight	3.32 kg	3.32 kg
Power Supply	100-240 VAC, 50-60 Hz	Yes	Yes
	DC Power Input (48-60 V)	Yes	Yes
	Max System Power Consumption (Watts)	21.48 W	21.48 W
Environmental	Operating Temperature	0°C to 50°C	-10°C to 65°C
	Storage Temperature	-40°C to 70°C	-40°C to 70°C
	Operating Humidity (non-condensing)	10% to 90%	10% to 90%
	Storage Humidity (non-condensing)	10% to 90%	10% to 90%
	Environmental Regulation Compliance: WEEE	Yes	Yes
	Environmental Regulation Compliance: RoHS	Yes	Yes
Certification	FCC Class A	Yes	Yes
	CE	Yes	Yes
	Safety Compliance: CB	Yes	Yes
	Safety Compliance: UL	Yes	Yes

## Features

### L2 Features

- Tri-speed (10/100/1000BASE-T) copper interfaces
- Auto-negotiation for port speed and duplex mode
- Auto MDI/MDI-X
- 100 M/1 G fiber interface
- SFP ports support:
  - IEEE802.3 100BASE-FX
  - IEEE 802.3z (1000BASE-SX/LX/LHX/ZX) transceivers
- Transceiver-threshold current/rx-power/temperature/tx-power/voltage/high-low alarm and warning
- Digital Diagnostic Monitoring (DDM) on SFP port only
- Flow Control:
  - IEEE 802.3x for full duplex mode
  - Back-Pressure for half duplex mode
- Jumbo Frames: 12 KB
- Broadcast/Multicast/ Unknown Unicast Storm Control
- Spanning Tree Protocol:
  - IEEE 802.1D Spanning Tree Protocol (STP)
  - IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
  - IEEE 802.1s Multiple Spanning Tree Protocol (MSTP), 64 instances
- Spanning-tree restricted-tcn
- Spanning-tree tc-prop-stop Stops propagation of topology change information
- BPDUGuard
- BPDUGuard filtering
- Root Guard
- BPDUGuard transparent
- Loopback detection
- Non-Spanning Tree Loopback detection
- ITU-T G.8032 Ethernet Ring Protection Switching:
  - Sub 50 msec convergence
  - Non-revertive operation mode
  - Multiple-ring topology
  - VLAN exclude/include in ERPS ring port
- VLANs:
  - Supports 4K VLAN
  - Port-based VLAN
  - IEEE 802.1Q VLAN
  - GVRP (256 VLAN)
  - IEEE 802.1v Protocol-based VLAN
  - IP Subnet-based VLAN
  - MAC-based VLAN
  - Traffic Segmentation
- L2 Virtual Private Networks (Q-in-Q):
  - Selective QinQ
  - VLAN Translation
  - L2 Protocol tunneling (xSTP, CDP, VTP and PVST+, LLDP)
  - CDP/PVST+ Filtering
- Link Aggregation:
  - Static Trunk
  - IEEE 802.3ad Link Aggregation Control Protocol
  - Trunk groups: 16, up to 8 GE ports per group
  - Load Balancing: SA+DA, SA, DA, SIP+DIP, SIP, DIP
  - Smart Link (Active-Standby LAG)
- IGMP Snooping:
  - IGMP v1/v2/v3 snooping
  - IGMP Proxy reporting
  - IGMP Filtering
  - IGMP Throttling
  - IGMP Immediate Leave
  - IGMP Querier
  - IGMP mrouter-forward mode
  - IGMP router-alert-option-check
  - IGMP router-port-expire-time
  - IGMP tcn-flood
  - IGMP tcn-query-solicit
  - IGMP unregistered-data-flood
- MVR (Multicast VLAN Registration): Supports 5 multicast VLANs
- Port mirroring with maximum 27 ports
- Remote port mirror (RSPAN)

### Security

- User Security for Enterprise:
  - IEEE 802.1X port based and MAC based authentication
  - Dynamic VLAN Assignment, Auto QoS
  - MAC authentication
  - Web authentication
  - Voice VLAN
  - Guest VLAN
- User Security for ISP/MSO:
  - L2/L3/L4 Access Control List supports 1 K
  - MAC Access control list (Source/Destination MAC, Ether type, Priority ID/ VLAN ID)
  - IP standard access control list (Source IP)
  - IP extended access control list (Source/Destination IP, Protocol, TCP/UDP port number)
  - DHCP Snooping
  - DHCP Option 82
  - DHCP Option 82 Relay
  - IP Source Guard
- Network Security:
  - IPv6 ACL
  - Port security
  - PPPoE IA
  - Dynamic ARP Inspection
  - CPU guard
  - CPU/Memory threshold and alarm
  - Denial of Service protection
    - echo-charge
    - smurf
    - tcp-flooding
    - tcp-null-scan
    - cp-syn-fin-scan
    - tcp-xmas-scan
    - udp-flooding
    - win-nuke
- Management Security:
  - Login Security
  - RADIUS authentication
  - RADIUS accounting
  - TACACS + authentication
  - TACACS + accounting
  - TACACS + authorization
  - Management Interface Access Filtering (SNMP, Web, Telnet)
  - SSH (v1.5/v2.0) for security Telnet
  - SSL for HTTPS
  - SNMPv3

### Green Ethernet

- IEEE 802.3az Energy-Efficient Ethernet (EEE)

### OAM

- IEEE 802.3ah Link
- IEEE 802.1ag Connectivity Fault Management:
  - Connectivity check
  - Loopback
  - Linktrace
- ITU-T Y.1731 Performance and Throughput Management:
  - Frame Delay
  - Frame Delay variation

## Features

### QoS Features

Priority Queues: 8 hardware queues per port  
Traffic classification:  
IEEE 802.1p CoS  
IP Precedence  
DSCP  
MAC Access control list ( Source/Destination MAC, Ether type, Priority ID/ VLAN ID )  
IP Standard access control list (Source IP)  
IP extended access control list (Source/Destination IP, Protocol, TCP/UDP port number)  
Traffic Scheduling:  
Strict Priority  
Weighted Round Robin  
Strict + WRR  
Ingress policy map (police rate, remark CoS)  
Egress policy map (police rate, remark CoS/DSCP)  
Rate Limiting (Ingress and Egress, per port base):  
GE: Resolution 64Kbps ~ 1,000Mbps  
Auto Traffic Control

### IPv6 Features

IPv4/IPv6 Dual Protocol stack  
IPv6 Address Types Stack: Unicast  
IPv6 Neighbor Discovery (RFC4861):  
Duplicate address  
Address resolution  
Unreachable neighbor detection  
Stateless auto-configuration  
Manual configuration  
Remote IPv6 ping  
IPv6 Telnet support  
HTTP over IPv6  
SNMP over IPv6  
IPv6 Syslog support  
IPv6 TFTP support  
IPv6 MLD filter: MLD max-groups (throttling)  
IPv6 ND snooping  
MLD Snooping v1/v2  
IPv6 source guard  
DHCPv6 snooping  
MVR6

### Routing

IPv4 Static Route  
IPv6 Static Route  
32 IP interface  
256 IPv4/IPv6 static route  
RIP v1/v2  
Traceroute  
Traceroute6

### Management

Switch Management:  
CLI via console port or Telnet  
Web management  
SNMP v1, v2c, v3  
SNMP trap for IPv4/IPv6  
IP clustering (32 members)  
Firmware & Configuration:  
Firmware upgrade via TFTP/HTTP/FTP server  
Dual images  
Multiple configuration files  
Configuration file upload/download via TFTP/HTTP/FTP server  
Firmware auto upgrade  
RMON (groups 1, 2, 3 and 9)  
BOOTP, DHCP client for IP address assignment  
ZTP  
DHCP dynamic provision option 66,67  
DHCPv6 dynamic provision 59,60  
DHCPv6 DUID type 2  
SNTP/NTPV4  
DNS client  
Event/Error Log  
Syslog  
SMTP  
Supports LLDP (802.1ab)  
sFlow v4, v5, IPv4/IPv6  
Cable diagnostics  
Traceroute  
Traceroute6  
DHCP server (8 pools, 512 IP addresses)  
(Optional) ECView Pro, a powerful network management software that maximizes the managed capabilities of Edgecore devices with:  
Topology management  
Performance management  
Configuration management  
Event management  
SNMP management

### Safety

UL (CSA 22.2. NO 60950-1 & UL60950-1)  
CB (IEC60950-1)

### Electromagnetic Compatibility

CE Mark  
FCC Class A  
CISPR Class A  
BSMI

### Environmental Specifications

Temperature:  
0°C to 50°C (180 W PoE budget) standard operation  
0°C to 55°C (120 W PoE budget)  
≤ 70W PoE budget, fanless for silent operation  
-40°C to 70°C (Non-Operating)  
Humidity: 10% to 90% (Non-condensing)

### Power Supply

Power input  
100 to 240 VAC, 50/60 Hz  
AC/DC: 90VAC~300VAC, 50/60 Hz  
Dying gasp

### Warranty

Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

## Features

### For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

### About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore data center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2018 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

## Ordering Information

Optional Accessories	Product Description
ET3201-FXP	100BASE-FX Multi mode LC Duplex SFP transceiver, up to 2 km (1310 nm)
ET3201-FX20	100BASE-FX Single mode LC Duplex SFP transceiver, up to 20 km (1310 nm)
ET3203-BX20	100BASE-FX Single mode LC Simplex SFP transceiver, up to 20 km Tx1310 nm/Rx1550 nm
ET3203-BX20D	100BASE-FX Single mode LC Simplex SFP transceiver, up to 20 km Tx1550 nm/Rx1310 nm
ET4201-LX5	1Gbps, Small Form Factor Pluggable (Distance: 5 km; Wavelength: 1310 nm)
ET4201-LX15	1Gbps, Small Form Factor Pluggable (Distance: 15 km; Wavelength: 1310 nm)
ET4201-LHX	1Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1310 nm)
ET4201-ZX	1Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm)
ET4202-SX	1Gbps, Small Form Factor Pluggable (Distance: 550 m; Wavelength: 850 nm, DDM)
ET4202-LX	1Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm, DDM)
ET5402-SR	10Gbps, Small Form Factor Pluggable (Distance: 300 m; Wavelength: 850 nm)
ET5402-LR	10Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)
ET5402-ER	10Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1550 nm)
ECView Pro	Network Management Software